

## ANTI-SLIP VERSE CREAM RECT 120X120

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP      |
|----------------|-----------|----------------|------------|
| <b>A044309</b> | 120X120   | 8,10           | PC BIA UGL |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requirements |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                         |
|---------------------------|-----------------|-------------------------|
| Water absorption capacity | EN ISO 10545-03 | < 0,5%                  |
| Flexion resistance        | EN ISO 10545-04 | => 35 N/mm <sup>2</sup> |
| Deep abrasion resistance  | EN ISO 10545-06 | <175mm3                 |
| Thermal shock resistance  | EN ISO 10545-09 | It stands the test      |
| Frost resistance          | EN ISO 10545-12 | It stands the test      |

### CHEMICAL PROPERTIES

|                                                        |                 |    |
|--------------------------------------------------------|-----------------|----|
| Resistance to acids                                    | EN ISO 10545-13 | UB |
| Resistance to alcalis                                  | EN ISO 10545-13 | UB |
| Resistance to cleaning products                        | EN ISO 10545-13 | UB |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | UB |
| Stains resistance                                      | EN ISO 10545-14 | 3  |

### ANTI-SLIP CHARACTERISTICS

|                            |                |         |
|----------------------------|----------------|---------|
| Slip resistance (Rd)       | UNE-EN 16165-C | Class 3 |
| Slip resistance (R)        | EN 16165-B     | R11     |
| Slip resistance (barefeet) | EN 16165-A     | C       |
| Slip resistance (DCOF)     | ANSI A326.3    | >0,42   |