

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

FLOW WHITE RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

FLOW MIST RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

FLOW DOVE RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

PRISM WHITE RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

PRISM MIST RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

PRISM DOVE RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

ENEА WHITE RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requirements
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

ENECA MIST RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requirements
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

ENEADOVE RECT. 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requirements
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

DECOR SET(3) BOTANIC 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm2
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

DECOR TRIANGLE DOVE 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

DECOR CHANDELIER I 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

DECOR TRIANGLE WHITE 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT

APE

best for you

Technical characteristics report

Serial: FLOW

Wall Tile

DECOR CHANDELIER II 33,3X100

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments
Water absorption capacity	EN ISO 10545-03	>10%
Flexion resistance	EN ISO 10545-04	=> 20 N/mm ²
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

QUALITY DEPARTMENT