



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

ANTI-SLIP PLITVICE BEIGE

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (750 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	3



Technical characteristics report

Serial: PLITVICE

Size: 15x90

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

ANTI-SLIP PLITVICE BROWN

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$\leq 0,5\%$
Flexion resistance	EN ISO 10545-04	$\geq 35 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (750 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	3



Technical characteristics report

Serial: PLITVICE

Size: 15x90

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

ANTI-SLIP PLITVICE CREAM

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2.100 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	3



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

ANTI-SLIP PLITVICE GREY

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (1500 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	3



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

ANTI-SLIP PLITVICE TORTOLA

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (1.500 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	3



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

ANTI-SLIP PLITVICE WHITE

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (6.000 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	3



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

PLITVICE BEIGE

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2100 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	1



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

PLITVICE BROWN

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (750 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	1



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain Norm: UNE-EN 14411 Group: Bla

PLITVICE CREAM

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2.100 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	1



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

PLITVICE GREY

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (1500 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	1



Technical characteristics report

Serial: PLITVICE	Size: 15x90
------------------	-------------

Gres Porcelain	Norm: UNE-EN 14411	Group: Bla
----------------	--------------------	------------

PLITVICE TORTOLA

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	≤ 0,5%
Flexion resistance	EN ISO 10545-04	≥ 35 N/mm2
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (1.500 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	1



Technical characteristics report

Serial: PLITVICE

Size: 15x90

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

PLITVICE WHITE

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$\leq 0,5\%$
Flexion resistance	EN ISO 10545-04	$\geq 35 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (6.000 rev.)
Hardness degree, method MOHS	UNE 67-101-92	7
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	1