



Technical characteristics report

Serial: WONDER	Size: 60x60
----------------	-------------

Floor tile - Gres Porcelain Norm: UNE-EN 14411 Group: Bla

Wonder Crema

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 35 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	III
Hardness degree, method MOHS	UNE 67-101-92	-
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLB
Resistance to alcalis	EN ISO 10545-13	GLB
Resistance to cleaning products	EN ISO 10545-13	GB
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GB
Stains resistance	EN ISO 10545-14	5



Technical characteristics report

Serial: WONDER	Size: 60x60
----------------	-------------

Floor tile - Gres Porcelain Norm: UNE-EN 14411 Group: Bla

Wonder Azul

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 35 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	III
Hardness degree, method MOHS	UNE 67-101-92	-
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLB
Resistance to alcalis	EN ISO 10545-13	GLB
Resistance to cleaning products	EN ISO 10545-13	GB
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GB
Stains resistance	EN ISO 10545-14	5



Technical characteristics report

Serial: WONDER	Size: 60x60
----------------	-------------

Floor tile - Gres Porcelain Norm: UNE-EN 14411 Group: Bla

Wonder Blanco

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 35 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	III
Hardness degree, method MOHS	UNE 67-101-92	-
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLB
Resistance to alcalis	EN ISO 10545-13	GLB
Resistance to cleaning products	EN ISO 10545-13	GB
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GB
Stains resistance	EN ISO 10545-14	5



Technical characteristics report

Serial: WONDER	Size: 29.5X90
----------------	---------------

Wall tiles with white body. Dry pressed ceramic tiles for interior walls.

It accomplishes norm: UNE-EN 14411

Group: BIII

Name, Test		European norm	Value
Size, thickness, side straightness, flatness, orthogonality		UNE-EN 14411	It accomplishes all requirements
Water absorption capacity		EN ISO 10545-03	> 10 %
Flexion resistance		EN ISO 10545-04	> 15 N/mm ²
Thermic impact resistance		EN ISO 10545-9	It stands the test
Cracking resistance		EN ISO 10545-11	It stands the test
Resistance to acids		EN ISO 10545-13	GLB
Resistance to bases		EN ISO 10545-13	GLB
Resistance to cleaning products and chemical products for swimming pool water		EN ISO 10545-13	GB
Stains resistance		EN ISO 10545-14	5
Size (mm)	295x901	Thickness (mm)	12.0