

Technical characteristics report

Serial: Tratto

Size: 20x60

Wall tiles with red body. Dry pressed ceramic tiles for interior walls.

It accomplishes norm: UNE-EN 14411

Group: BIII

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	> 12 %
Flexion resistance	EN ISO 10545-04	> 23 N/mm ²
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

Technical characteristics report

Serial: Tratto

Size: 45x45

TRATTO BEIGE

Floor tiles with red body. Dry pressed ceramic tiles for interior floors and walls.

It accomplishes norm: UNE-EN 14411

Group: BIIa

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$3\% < E \leq 6\%$
Flexion resistance	EN ISO 10545-04	$> 27 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2100 rev)
Hardness degree, method MOHS	UNE 67-101-92	≥ 6
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

Technical characteristics report

Serial: Tratto

Size: 45x45

TRATTO PEARL

Floor tiles with red body. Dry pressed ceramic tiles for interior floors and walls.

It accomplishes norm: UNE-EN 14411

Group: BIIa

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$3\% < E \leq 6\%$
Flexion resistance	EN ISO 10545-04	$> 27 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2100 rev)
Hardness degree, method MOHS	UNE 67-101-92	≥ 6
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

Technical characteristics report

Serial: Tratto

Size: 45x45

TRATTO GREY

Floor tiles with red body. Dry pressed ceramic tiles for interior floors and walls.

It accomplishes norm: UNE-EN 14411

Group: BIIa

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$3\% < E \leq 6\%$
Flexion resistance	EN ISO 10545-04	$> 27 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (1500 rev)
Hardness degree, method MOHS	UNE 67-101-92	≥ 4
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

Technical characteristics report

Serial: Tratto

Size: 45x45

TRATTO MIEL

Floor tiles with red body. Dry pressed ceramic tiles for interior floors and walls.

It accomplishes norm: UNE-EN 14411

Group: BIIa

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$3\% < E \leq 6\%$
Flexion resistance	EN ISO 10545-04	$> 27 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	III (750 rev)
Hardness degree, method MOHS	UNE 67-101-92	≥ 4
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5