



DECLARATION OF PERFORMANCE

No. APE 01-07-2013 Bla

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external, floorings and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 01-07-2013
Place and date of issue

Signature



DECLARATION OF PERFORMANCE

No. APE 25-05-2015 Bla (3.5 mm.)

7. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5 \%$, reinforced with fiberglass net on the back (multilayer material)
8. Intended use(s)
For internal and external, floorings and wall finishes
9. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN
10. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
11. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
12. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2fl-s1 / A1-s1,d0	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	NPD (*)	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C1	$\geq 0,5 \text{ N/mm}^2$	
Cementitious adhesive, type C2	$\geq 1 \text{ N/mm}^2$	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

(*) Not applicable for multilayer material

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 25-05-2015
Place and date of issue

Signature



DECLARATION OF PERFORMANCE

No. APE 02-01-2019 Bla (5.6mm.)

13. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5 \%$
14. Intended use(s)
For internal and external, floorings and wall finishes
15. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN
16. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
17. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
18. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL} – A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	≥ 700 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2S1/C2S2	≥ 1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 02-01-2019
Place and date of issue

Signature



DECLARATION OF PERFORMANCE

No. APE 01-07-2013 Bib

19. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$
20. Intended use(s)
For internal floorings
21. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN
22. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
23. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
24. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 100 N	
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 01-07-2013
Place and date of issue

Signature



DECLARATION OF PERFORMANCE

No. APE 01-07-2013 B1a

25. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$
26. Intended use(s)
For internal floorings
27. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN
28. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
29. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
30. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 100 N	
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 01-07-2013
Place and date of issue

Signature



DECLARATION OF PERFORMANCE

No.APE 01-07-2013 BIII

31. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b > 10\%$
32. Intended use(s)
For internal wall finishes
33. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN
34. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
35. Name and identification number of notified laboratory, if relevant – *not applicable*
Task(s) carried out
AVCP system
Document issued and date of issue
36. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C1	>0,5 N/mm²	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 01-07-2013
Place and date of issue

Signature



DECLARATION OF PERFORMANCE

No. APE 01-10-2015 Klinker

43. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
**Ceramic tiles, extruded for internal and external flooring and wall finishes,
with water absorption $E_b \leq 3\%$**
44. Intended use(s)
For internal and external, floorings and wall finishes
45. Name or registered trade mark, and contact address of the manufacturer
APE CERÁMICA, S.L.U.
**Ciudad del Transporte C/Luxemburgo, parcela 46
12006 Castellón, SPAIN**
46. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
47. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
48. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	>1300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C1	$\geq 0,5 \text{ N/mm}^2$	
Cementitious adhesive, type C2	$\geq 1 \text{ N/mm}^2$	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Name and function
David López (Quality manager)

Castellón, 01-10-2015
Place and date of issue

Signature