

**UK DECLARATION OF CONFORMITY**

**No. APE 01-07-2013 Bla**

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with low water absorption  $E_b \leq 0,5 \%$**
2. Intended use(s)  
**For internal and external, floorings and wall finishes**
3. Name or registered trade mark, and contact address of the manufacturer  
**APE CERÁMICA, S.L.U.**  
**Ciudad del Transporte C/Luxemburgo, parcela 46**  
**12006 Castellón, SPAIN**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**Systems 4**
5. Name and identification number of notified laboratory, if relevant – **not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue
6. Declared performances

| Essential characteristics              | Performance           | Harmonised technical specification |
|--|-----------------------|------------------------------------|
| Reaction to fire                       | A1 <sub>FL</sub> /A1  | <b>EN 14411:2012</b>               |
| Release of dangerous substance, for:   |                       |                                    |
| - Cadmium                              | NPD                   |                                    |
| - Lead                                 | NPD                   |                                    |
| Breaking strength                      | > 1 300 N             |                                    |
| Slipperiness                           | NPD                   |                                    |
| Tactility                              | NPD                   |                                    |
| Bond strength/adhesion, for:           |                       |                                    |
| Cementitious adhesive, type C2         | > 1 N/mm <sup>2</sup> |                                    |
| Thermal shock resistance               | Pass                  |                                    |
| Durability for:                        |                       |                                    |
| - internal use:                        | Pass                  |                                    |
| - external use: freeze-thaw resistance | Pass                  |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function  
David López (Quality manager)

Castellón, 01-01-2021  
Place and date of issue

Signature



**UK DECLARATION OF CONFORMITY**

**No. APE 02-01-2019 Bla (6mm.)**

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with low water absorption  $E_b \leq 0,5 \%$**
2. Intended use(s)  
**For internal and external, floorings and wall finishes**
3. Name or registered trade mark, and contact address of the manufacturer  
**APE CERÁMICA, S.L.U.**  
**Ciudad del Transporte C/Luxemburgo, parcela 46**  
**12006 Castellón, SPAIN**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**Systems 4**
5. Name and identification number of notified laboratory, if relevant – **not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue
6. Declared performances

| Essential characteristics                   | Performance                 | Harmonised technical specification |
|---|-----------------------------|------------------------------------|
| <b>Reaction to fire</b>                     | <b>A1<sub>FL</sub> – A1</b> | <b>EN 14411:2012</b>               |
| <b>Release of dangerous substance, for:</b> |                             |                                    |
| - Cadmium                                   | <b>NPD</b>                  |                                    |
| - Lead                                      | <b>NPD</b>                  |                                    |
| <b>Breaking strength</b>                    | <b>≥ 700 N</b>              |                                    |
| <b>Slipperiness</b>                         | <b>NPD</b>                  |                                    |
| <b>Tactility</b>                            | <b>NPD</b>                  |                                    |
| <b>Bond strength/adhesion, for:</b>         |                             |                                    |
| Cementitious adhesive, type C2S1/C2S2       | <b>≥ 1 N/mm<sup>2</sup></b> |                                    |
| <b>Thermal shock resistance</b>             | <b>Pass</b>                 |                                    |
| <b>Durability for:</b>                      |                             |                                    |
| - internal use:                             | <b>Pass</b>                 |                                    |
| - external use: freeze-thaw resistance      | <b>Pass</b>                 |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function  
David López (Quality manager)

Castellón, 01-01-2021  
Place and date of issue

Signature





**UK DECLARATION OF CONFORMITY**  
**No. APE 01-07-2013 Bib**

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $0,5% < E_b \leq 3%$**
2. Intended use(s)  
**For internal floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**APE CERÁMICA, S.L.U.**  
**Ciudad del Transporte C/Luxemburgo, parcela 46**  
**12006 Castellón, SPAIN**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**Systems 4**
5. Name and identification number of notified laboratory, if relevant – **not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue
6. Declared performances

| Essential characteristics            | Performance      | Harmonised technical specification |
|--------------------------------------|------------------|------------------------------------|
| Reaction to fire                     | A1 <sub>FL</sub> | EN 14411:2012                      |
| Release of dangerous substance, for: |                  |                                    |
| - Cadmium                            | NPD              |                                    |
| - Lead                               | NPD              |                                    |
| Breaking strength                    | > 1 100 N        |                                    |
| Slipperiness                         | NPD              |                                    |
| Tactility                            | NPD              |                                    |
| Durability for:                      |                  |                                    |
| - internal use:                      | Pass             |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.  
Signed for and on behalf of the manufacturer by:

Name and function  
David López (Quality manager)

Castellón, 01-01-2021  
Place and date of issue

Signature

**UK DECLARATION OF CONFORMITY**

**No. APE 01-07-2013 B1a**

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $3% < E_b \leq 6%$**
2. Intended use(s)  
**For internal floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**APE CERÁMICA, S.L.U.**  
**Ciudad del Transporte C/Luxemburgo, parcela 46**  
**12006 Castellón, SPAIN**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**Systems 4**
5. Name and identification number of notified laboratory, if relevant – **not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue

6. Declared performances

| Essential characteristics                   | Performance            | Harmonised technical specification |
|---|------------------------|------------------------------------|
| <b>Reaction to fire</b>                     | <b>A1<sub>FL</sub></b> | <b>EN 14411:2012</b>               |
| <b>Release of dangerous substance, for:</b> |                        |                                    |
| - Cadmium                                   | <b>NPD</b>             |                                    |
| - Lead                                      | <b>NPD</b>             |                                    |
| <b>Breaking strength</b>                    | <b>&gt; 1 100 N</b>    |                                    |
| <b>Slipperiness</b>                         | <b>NPD</b>             |                                    |
| <b>Tactility</b>                            | <b>NPD</b>             |                                    |
| <b>Durability for:</b>                      |                        |                                    |
| - internal use:                             | <b>Pass</b>            |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function  
David López (Quality manager)

Castellón, 01-01-2021  
Place and date of issue

Signature





## UK DECLARATION OF CONFORMITY

No.APE 01-07-2013 BIII

1. Unique identification code of the product type  
Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$**
2. Intended use(s)  
**For internal wall finishes**
3. Name or registered trade mark, and contact address of the manufacturer  
**APE CERÁMICA, S.L.U.**  
**Ciudad del Transporte C/Luxemburgo, parcela 46**  
**12006 Castellón, SPAIN**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**Systems 4**
5. Name and identification number of notified laboratory, if relevant – **not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue
6. Declared performances

| Essential characteristics                   | Performance                     | Harmonised technical specification |
|---|---------------------------------|------------------------------------|
| <b>Reaction to fire</b>                     | <b>A1</b>                       | <b>EN 14411:2012</b>               |
| <b>Release of dangerous substance, for:</b> |                                 |                                    |
| - Cadmium                                   | <b>NPD</b>                      |                                    |
| - Lead                                      | <b>NPD</b>                      |                                    |
| <b>Bond strength/adhesion, for:</b>         |                                 |                                    |
| Cementitious adhesive, type C1              | <b>&gt;0,5 N/mm<sup>2</sup></b> |                                    |
| <b>Durability for:</b>                      |                                 |                                    |
| - internal use:                             | <b>Pass</b>                     |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.  
Signed for and on behalf of the manufacturer by:

Name and function  
David López (Quality manager)

Castellón, 01-01-2021  
Place and date of issue

Signature

**UK DECLARATION OF CONFORMITY**

**No. APE 01-10-2015 Klinker**

1. Unique identification code of the product type  
 Type, batch or serial number or any other element allowing identification of the product  
**Ceramic tiles, extruded for internal and external flooring and wall finishes,  
 with water absorption  $E_p \leq 3 \%$**
2. Intended use(s)  
**For internal and external, floorings and wall finishes**
3. Name or registered trade mark, and contact address of the manufacturer  
**APE CERÁMICA, S.L.U.  
 Ciudad del Transporte C/Luxemburgo, parcela 46  
 12006 Castellón, SPAIN**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**Systems 4**
5. Name and identification number of notified laboratory, if relevant – **not applicable**  
 Task(s) carried out  
 AVCP system  
 Document issued and date of issue

6. Declared performances

| Essential characteristics                   | Performance                                 | Harmonised technical specification |
|---|---|------------------------------------|
| <b>Reaction to fire</b>                     | <b>A1<sub>FL</sub>/A1</b>                   | <b>EN 14411:2012</b>               |
| <b>Release of dangerous substance, for:</b> |   |                                    |
| - Cadmium                                   | <b>NPD</b>                                  |                                    |
| - Lead                                      | <b>NPD</b>                                  |                                    |
| <b>Breaking strength</b>                    | <b>&gt;1300 N</b>                           |                                    |
| <b>Slipperiness</b>                         | <b>NPD</b>                                  |                                    |
| <b>Tactility</b>                            | <b>NPD</b>                                  |                                    |
| <b>Bond strength/adhesion, for:</b>         |   |                                    |
| Cementitious adhesive, type C1              | <b><math>\geq 0,5 \text{ N/mm}^2</math></b> |                                    |
| Cementitious adhesive, type C2              | <b><math>\geq 1 \text{ N/mm}^2</math></b>   |                                    |
| <b>Thermal shock resistance</b>             | <b>Pass</b>                                 |                                    |
| <b>Durability for:</b>                      |   |                                    |
| - internal use:                             | <b>Pass</b>                                 |                                    |
| - external use: freeze-thaw resistance      | <b>Pass</b>                                 |                                    |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Name and function  
 David López (Quality manager)

Castellón, 01-01-2021  
 Place and date of issue

Signature

